

SANHO CHEMICAL CO., LTD. 1, ZHONGSHAN S. RD., LUZHU DIST., KAOHSIUNG CITY. TEL: 886-7-6962211~3 FAX : 886-7-6976993 (Sales) FAX: 886-7-6961782 (Export)

http://www.sanho.com.tw E-mail: sanho@sanho.com.tw E-mail : sanho@so-net.net.tw

KINGMIDE 530

KINGMIDE 530 is a fatty polyamide resin whose major applications are in the rotogravure printing inks and as the "gelling agent" in thixotropic alkyd varnishes.

The followings are the major characteristics of the KINGMIDE 530 as used in a rotogravure ink formulation;

- (a). excellent adhesion to a wide variety of substrates, such as; polyethylene (treated,), polypropylene (treated,), cellophane, aluminum fall and glassines.
- (b). rub resistance.
- (c). blocking and smearing resistance.
- (d). high water resistance.
- (e). high gloss.

1. SALES SPECIFICATIONS

Softening Point(°C)	: 110±5
Viscosity (Gardner-Holdt /25°C)	: *C~F
Color (Gardner)	: *10 Max
Acid Value (mg-KOH / gm)	:7 Max
	· 2 M

Amine Value (mg-KOH / gm) : 3 Max

* Viscosity and Color of the KINGMIDE 530 are of 40% solution in Toluene/ Isopropanol (7:3)

2. THE WAY OF PACKING

20 kg net, paper bag.

3. USAGE AND STORE

Keep the container tightly seal and store the materials in a cool and dry place away from open flames