SANHO CHEMICAL CO., LTD.
NO. 1, ZHONGSHAN S. RD., LUZHU DIST., KAOHSIUNG CITY, TAIWAN.
TEL：886-7-6962211~3 http：// www.sanho.com.tw
FAX：886-7-6976993 (Sales) E-mail：sanho@sanho.com.tw
FAX：886-7-6961782 (Export) E-mail：sanho@so-net.net.tw

KIGMIDE H-130

KINGMIDE H-130 is a high molecular weight polyamide resin especially designed for hot melt-adhesive use. KINGMIDE H-130 is easy to soluble in mixed organic solvent –such as toluene and alcohol type solvent. This resin has the characteristics of good colour and high softening point than#KINGMIDE120, it is suitable for applications electric parts, package, were high heat resistance and high adhesive strength and good toughness are particularly needed.

1. SALES SPECIFICATIONS

Appearance	：Small pellet with amber color.
Softening Point (℃)	：130 ± 5
Viscosity (mPa・s / 200℃)	：2,000 ~ 4,000
Color (Gardner)	：10 Max.
Acid Value (mg-KOH / gm)	：7 Max.
Amine Value (mg-KOH / gm)	：3 Max.

2. PHYSICAL PROPERTIES (MECHANICAL STRENGTH)

Tensile Strength (kgf / cm^2)	：55± 10
Yield Strength (kgf / cm^2)	：83± 10
Elongation (%)	：450± 10
Water Absorption after 7 days(%)	：0.4
Application temperature (℃)	：180~200

3. PACKAGING

20 kg net, paper bag.