



SANHO CHEMICAL CO., LTD.

NO. 1, ZHONGSHAN S. RD., LUZHU DIST., KAOHSIUNG CITY, TAIWAN.

TEL : 886-7-6962211~3

http : // www.sanho.com.tw

FAX : 886-7-6976993 (Sales)

E-mail : sanho@sanho.com.tw

FAX : 886-7-6961782 (Export)

E-mail : sanho@so-net.net.tw

TOHMIDE 560

TOHMIDE 560 is a low melting viscosity polyamide resin especially designed for hot melt-adhesive use. this resin has the characteristics of high softening point, and high peel strength 、 good storage stability of molten resin in heating - tank of application equipment under heating process ,if blended TOHMIDE 560 with an another polyamide hot melt can achieve an another higher bonding performance ◦

1. SALES SPECIFICATIONS

Appearance	: Brown-pellet amber color.
Viscosity (mPa · s / 200°C)	: 200 ~ 400
Color (Gardner)	: 12 Max.
Softening Point (°C)	: 160 ± 5

2. PHYSICAL PROPERTIES (MECHANICAL STRENGTH)

Tensile Strength (kgf / cm ²)	: 46± 10
Yield Strength (kgf / cm ²)	: 46± 10
Elongation (%)	: 46± 10
Water Absorption after 7 days(%)	: 1.7
Application temperature (°C)	: 180~200

3. PACKAGING

20 kg net, paper bag.